

# MATERIAL SAFETY DATA SHEET

MSDS Name: KALEX 16552 PART A  
MSDS Number: 16552-1  
Version Number: E  
MSDS Date: JUN-23-2005  
Page Number: 1 of 6

---

## SECTION I - PRODUCT AND COMPANY INFORMATION

Product Name: KALEX 16552 PART A  
Hazard Rating: Health: 3 Fire: 1 Reactivity: 0 PPI:

Company Identification: ROYAL ADHESIVES & SEALANTS LLC  
600 CORTLANDT STREET  
BELLEVILLE NJ 07109-3384

Contact: BRUCE WEINMAN  
Telephone/Fax: (973) 751-3000 (973) 751-8407  
Emergency Phone (24 Hour): ENVIRONMENTAL SPECIALIST  
(973) 751-3000  
Chemtrec (24 Hour): (800) 424-9300  
Preparer: B. WEINMAN  
ENVIRONMENTAL SPECIALIST

Product Class: POLYMERIC DIISOCYANATE  
Trade Name: KALEX 16552 PART A  
Product Code: 16552-1

## SECTION II - INGREDIENT AND HAZARD INFORMATION

Hazardous Ingredients CAS Number

4,4'-DIPHENYLMETHANE DIISOCYANATE 101-68-8

\*\*\* ALL Ingredients in this product are listed in the T.S.C.A. Inventory

## SECTION III - HAZARDS IDENTIFICATION

### HEALTH HAZARD INFORMATION:

#### EYE CONTACT:

MAY CAUSE EYE IRRITATION. CORNEAL DAMAGE POSSIBLE.

#### SKIN CONTACT:

MAY CAUSE IRRITATION. PROLONGED OR REPEATED CONTACT MAY CAUSE RASH, REDDENING, SWELLING, AND IN SOME CASES, SKIN SENSITIZATION.

#### INHALATION:

AT ROOM TEMPERATURE VAPORS ARE MINIMAL DUE TO LOW VAPOR PRESSURE. HOWEVER, HEATING OR SPRAYING MAY GENERATE VAPOR CONCENTRATIONS SUFFICIENT TO CAUSE IRRITATION. EXCESSIVE EXPOSURE MAY CAUSE

---

# MATERIAL SAFETY DATA SHEET

MSDS Name: KALEX 16552 PART A  
MSDS Number: 16552-1  
Version Number E  
MSDS Date: JUN-23-2005  
Page Number: 2 of 6

---

IRRITATION OF THE EYES, UPPER RESPIRATORY TRACT, AND LUNGS. MAY CAUSE RESPIRATORY SENSITIZATION IN SUSCEPTIBLE INDIVIDUALS. MDI CONCENTRATIONS BELOW THE EXPOSURE GUIDELINES MAY CAUSE ALLERGIC RESPIRATORY REACTIONS IN INDIVIDUALS ALREADY SENSITIZED. SYMPTOMS MAY INCLUDE COUGHING, DIFFICULT BREATHING AND A FEELING OF TIGHTNESS IN THE CHEST. EFFECTS MAY BE DELAYED. IMPAIRED LUNG FUNCTION (DECREASED VENTILATORY CAPACITY) HAS BEEN ASSOCIATED WITH OVEREXPOSURE TO ISOCYANATES.

#### INGESTION:

MAY CAUSE IRRITATION AND CORROSIVE ACTION IN THE MOUTH, STOMACH TISSUE AND DIGESTIVE TRACT. SYMPTOMS CAN INCLUDE SORE THROAT, ABDOMINAL PAIN, NAUSEA, VOMITING AND DIARRHEA.

#### OTHER HEALTH INFORMATION (POLYMERIC MDI CAS 101-68-8):

TISSUE INJURY IN THE UPPER RESPIRATORY TRACT AND LUNGS HAS BEEN OBSERVED IN LABORATORY ANIMALS AFTER REPEATED EXCESSIVE EXPOSURES TO MDI/POLYMERIC MDI AEROSOLS.

LUNG TUMORS HAVE BEEN OBSERVED IN LABORATORY ANIMALS EXPOSED TO AEROSOL DROPLETS OF MDI/POLYMERIC MDI FOR THEIR LIFETIME. TUMORS OCCURRED CONCURRENTLY WITH RESPIRATORY IRRITATION AND LUNG INJURY. CURRENT EXPOSURE GUIDELINES ARE EXPECTED TO PROTECT AGAINST THESE EFFECTS REPORTED FOR MDI.

IN LABORATORY ANIMALS, MDI/POLYMERIC MDI DID NOT PRODUCE BIRTH DEFECTS; OTHER FETAL EFFECTS OCCURRED ONLY AT HIGH DOSES WHICH WERE TOXIC TO THE MOTHER.

ANIMAL TESTS HAVE ALSO INDICATED THAT RESPIRATORY SENSITIZATION CAN RESULT FROM SKIN CONTACT WITH MDI. USE SKIN PROTECTION.

## SECTION IV - FIRST AID MEASURES

#### EYES:

WASH WITH FLOWING WATER IMMEDIATELY AND CONTINUOUSLY FOR 15 MINUTES. CONSULT MEDICAL PERSONNEL.

#### SKIN:

WASH WITH SOAP AND PLENTY OF WARM WATER.

#### INHALATION:

REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. IF BREATHING IS DIFFICULT, OXYGEN SHOULD BE ADMINISTERED BY QUALIFIED PERSONNEL. CALL A PHYSICIAN OR TRANSPORT TO A MEDICAL

---

# MATERIAL SAFETY DATA SHEET

MSDS Name: KALEX 16552 PART A  
MSDS Number: 16552-1  
Version Number E  
MSDS Date: JUN-23-2005  
Page Number: 3 of 6

---

FACILITY.  
INGESTION:  
IF SWALLOWED SEEK MEDICAL ATTENTION. DO NOT INDUCE VOMITING UNLESS DIRECTED TO DO SO BY MEDICAL PERSONNEL. GIVE NOTHING BY MOUTH IF PERSON IS UNCONSCIOUS OR HAVING CONVULSIONS.

## SECTION V - FIRE-FIGHTING MEASURES

Flammability Class IIIIB  
Flash Range: Not Available  
Pensky-Martens Closed Cup ASTM D 93  
>400F  
Explosive Range: Not Available

### FIRE-FIGHTING MEASURES:

WATER SPRAY  
DRY CHEMICAL  
FOAM  
CARBON DIOXIDE  
USE FULL TURNOUT GEAR INCLUDING SELF-CONTAINED BREATHING APPARATUS (SCBA).  
DURING A FIRE, POLYMERIC DIPHENYLMETHANE DIISOCYANATE (MDI) VAPORS AND OTHER IRRITATING, HIGHLY TOXIC GASES MAY BE GENERATED BY THERMAL DECOMPOSITION OR COMBUSTION. AT TEMPERATURES GREATER THAN 400F, POLYMERIC MDI CAN POLYMERIZE AND DECOMPOSE WHICH CAN CAUSE PRESSURE BUILD-UP IN CLOSED CONTAINERS. EXPLOSIVE RUPTURE IS POSSIBLE. THEREFORE, USE COLD WATER TO COOL FIRE-EXPOSED CONTAINERS.

## SECTION VI - ACCIDENTAL RELEASE MEASURES

### SPILLS:

SHUT OFF ALL IGNITION SOURCES AND DIKE SPILL TO CONTAIN AND PREVENT ENTRY INTO SEWERS OR WATER SOURCES. ABSORB SPILLED MATERIAL AND PLACE INTO OPEN TOP CONTAINERS. DO NOT MAKE PRESSURE TIGHT. TRANSPORT TO A WELL-VENTILATED AREA (OUTSIDE) AND TREAT WITH NEUTRALIZING SOLUTION CONSISTING OF A MIXTURE OF 85% WATER, 5% CONCENTRATED AMMONIUM HYDROXIDE AND 10% SODIUM CARBONATE. ADD ABOUT 10 PARTS OF NEUTRALIZER PER PART OF ISOCYANATE WITH MIXING. ALLOW TO STAND FOR 48 HOURS LETTING EVOLVED CARBON DIOXIDE TO ESCAPE. IF TEMPORARY CONTROL OF ISOCYANATE VAPOR IS REQUIRED, A BLANKET OF PROTEIN FOAM (AVAILABLE AT MOST

---

# MATERIAL SAFETY DATA SHEET

MSDS Name: KALEX 16552 PART A  
MSDS Number: 16552-1  
Version Number: E  
MSDS Date: JUN-23-2005  
Page Number: 4 of 6

---

FIRE DEPARTMENTS) MAY BE PLACED OVER THE SPILL.  
CONTROLLED INCINERATION. HANDLE IN COMPLIANCE WITH LOCAL, STATE,  
AND FEDERAL ENVIRONMENTAL PROTECTION AGENCY REGULATIONS.

## SECTION VII - HANDLING AND STORAGE

### STORAGE CONDITIONS:

STORE IN TIGHTLY CLOSED CONTAINERS TO PREVENT MOISTURE CONTAMINATION.  
DO NOT RESEAL IF CONTAMINATION IS SUSPECTED. OPTIMUM STORAGE  
TEMPERATURE IS 80F TO 100F.

## SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

### Occupational Exposure Limits

	ACGIH TLV	ACGIH TLV-C	ACGIH STEL	OSHA STEL	OSHA PEL
4,4'-DIPHENYLMETHANE DIISOCYANATE	0.0050 PPM	N/est	N/est	N/est	0.0200 PPM

### PERSONAL PROTECTIVE EQUIPMENT:

ATMOSPHERIC LEVELS SHOULD BE MAINTAINED BELOW THE EXPOSURE GUIDE  
LINE. WHEN RESPIRATORY PROTECTION IS REQUIRED FOR CERTAIN OPERATIONS,  
USE AN APPROVED POSITIVE-PRESSURE SUPPLIED-AIR RESPIRATOR. FOR  
EMERGENCY AND OTHER CONDITIONS WHERE THE EXPOSURE GUIDELINE MAY BE  
GREATLY EXCEEDED, USE AN APPROVED POSITIVE-PRESSURE SELF-CONTAINED  
BREATHING APPARATUS OR POSITIVE-PRESSURE AIRLINE WITH AUXILIARY  
SELF-CONTAINED AIR SUPPLY.  
THIS PRODUCT HAS POOR WARNING PROPERTIES, SINCE RECOGNITION OF AN ODOR  
IS FAR ABOVE THE TLV. OBSERVE OSHA REGULATIONS FOR RESPIRATOR USE (29  
CFR 1910.134).  
LOCAL EXHAUST IS RECOMMENDED.  
USE PROTECTIVE CLOTHING IMPERVIOUS TO THIS MATERIAL.  
SELECTION OF SPECIFIC ITEMS SUCH AS FACESHIELD, GLOVES, OR APRON  
WILL DEPEND ON OPERATION.  
CHEMICAL SPLASH GOGGLES. IN A SPLASH ENVIRONMENT CHEMICAL  
GOGGLES AND FULL FACE SHIELD SHOULD BE WORN.  
CHEMICAL RESISTANT PROTECTIVE CLOTHING TO MINIMIZE EXPOSURE.  
EYE WASH STATION AND SAFETY SHOWER SHOULD BE AVAILABLE FOR  
EMERGENCY USE.

## SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

Form: LIQUID  
Boiling Range: Not Available

---

# MATERIAL SAFETY DATA SHEET

MSDS Name: KALEX 16552 PART A  
MSDS Number: 16552-1  
Version Number: E  
MSDS Date: JUN-23-2005  
Page Number: 5 of 6

---

Vapor Pressure (mmHg): Not Available  
Melting Point: Not Applicable  
Evaporation Rate: Unavailable  
  
% Volatile: Not Available  
Specific Gravity: 1.24

## SECTION X - STABILITY AND REACTIVITY

Stability: This product is stable  
Hazardous Polymerization: Hazardous polymerization may occur

## SECTION XI - TOXICOLOGICAL INFORMATION

Lethal Dose Information (ppm)	Oral	Skin	Inhale	LC50
-------------------------------	------	------	--------	------

## SECTION XII - ECOLOGICAL INFORMATION

NO INFORMATION IS AVAILABLE.

## SECTION XIII - DISPOSAL CONSIDERATIONS

### RCRA CONSIDERATIONS:

THIS PRODUCT IF DISPOSED OF IN THE PURCHASED FORM IS NOT CONSIDERED RCRA HAZARDOUS.

## SECTION XIV - TRANSPORT INFORMATION

UN Number  
UN Pack Group  
UN Class  
ICAO/IATA Class: NOT REGULATED  
IMDG Class: NOT REGULATED  
Shipping Name: PLASTIC LIQUID, NOS  
ADR/RID Class: NOT REGULATED  
DOT Hazard Class  
Technical Name

## SECTION XV - REGULATORY INFORMATION

---

# MATERIAL SAFETY DATA SHEET

MSDS Name: KALEX 16552 PART A  
MSDS Number: 16552-1  
Version Number: E  
MSDS Date: JUN-23-2005  
Page Number: 6 of 6

---

## SARA TITLE III SECTION 313:

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right to Know Act of 1986 and of 40 CFR 372:

Chemical Name	CAS Number	%
4,4'-DIPHENYLMETHANE DIISOCYANATE	101-68-8	15 - 40

## TSCA STATUS:

ALL INGREDIENTS CONTAINED IN THIS PRODUCT ARE ON THE TSCA INVENTORY.

## SECTION XVI - OTHER INFORMATION

### DISCLAIMER:

ALTHOUGH THE INFORMATION AND RECOMMENDATIONS SET FORTH HEREIN (HEREINAFTER "INFORMATION") ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE CORRECT AS OF THE DATE HEREOF, ROYAL ADHESIVES & SEALANTS LLC MAKES NO REPRESENTATIONS AS TO THE COMPLETENESS OR ACCURACY THEREOF. INFORMATION IS SUPPLIED UPON THE CONDITION THAT THE PERSONS RECEIVING SAME WILL MAKE THEIR OWN DETERMINATION AS TO ITS SUITABILITY FOR THEIR PURPOSES PRIOR TO USE. IN NO EVENT WILL ROYAL ADHESIVES & SEALANTS LLC BE RESPONSIBLE FOR DAMAGES OF ANY NATURE WHATSOEVER RESULTING FROM THE USE OF OR RELIANCE UPON INFORMATION. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OF ANY NATURE ARE MADE HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT TO WHICH INFORMATION REFERS.

---

# MATERIAL SAFETY DATA SHEET

MSDS Name: KALEX 16552 PART B  
MSDS Number: 16552-2  
Version Number: F  
MSDS Date: JUN-20-2005  
Page Number: 1 of 5

---

## SECTION I - PRODUCT AND COMPANY INFORMATION

Product Name: KALEX 16552 PART B  
Hazard Rating: Health: 1 Fire: 1 Reactivity: 0 PPI:

Company Identification: ROYAL ADHESIVES & SEALANTS LLC  
600 CORTLANDT STREET  
BELLEVILLE NJ 07109-3384

Contact: BRUCE WEINMAN  
Telephone/Fax: (973) 751-3000 (973) 751-8407  
Emergency Phone (24 Hour): ENVIRONMENTAL SPECIALIST  
(973) 751-3000  
Chemtrec (24 Hour): (800) 424-9300  
Preparer: B. WEINMAN  
ENVIRONMENTAL SPECIALIST

Product Class: POLYOL  
Trade Name: KALEX 16552 PART B  
Product Code: 16552-2

## SECTION II - INGREDIENT AND HAZARD INFORMATION

Hazardous Ingredients	CAS Number
POLYBUTADIENE	TRADE SECRET
HYDRATED ALUMINA	TRADE SECRET
TRADE SECRET	TRADE SECRET
FUMED SILICA	TRADE SECRET

\*\*\* ALL Ingredients in this product are listed in the T.S.C.A. Inventory

---

# MATERIAL SAFETY DATA SHEET

MSDS Name: KALEX 16552 PART B  
MSDS Number: 16552-2  
Version Number F  
MSDS Date: JUN-20-2005  
Page Number: 2 of 5

---

## SECTION III - HAZARDS IDENTIFICATION

### EYE CONTACT:

(ACUTE) MAY RESULT IN IRRITATION. (CHRONIC) NONE KNOWN.

### SKIN CONTACT:

(ACUTE) MAY RESULT IN IRRITATION. (CHRONIC) NONE KNOWN.

### INHALATION:

(ACUTE) MAY RESULT IN RESPIRATORY IRRITATION. (CHRONIC) NONE KNOWN.

### INGESTION:

(ACUTE) MAY RESULT IN GASTRIC DISTURBANCES. (CHRONIC) NONE KNOWN.

## SECTION IV - FIRST AID MEASURES

### EYES:

IMMEDIATELY WASH WITH RUNNING WATER FOR AT LEAST 15 MINUTES. GET IMMEDIATE MEDICAL ATTENTION.

### SKIN:

WASH AFFECTED AREAS WITH SOAP AND PLENTY OF WATER. REMOVE AND LAUNDRER CONTAMINATED CLOTHING BEFORE REUSE. GET MEDICAL ATTENTION IF IRRITATION DEVELOPS.

### INHALATION:

MOVE PERSON TO FRESH AIR. AID IN BREATHING, GIVE OXYGEN IF NECESSARY. GET IMMEDIATE MEDICAL ATTENTION.

### INGESTION:

DRINK TWO GLASSES OF WATER AND IMMEDIATELY INDUCE VOMITING. NEVER GIVE FLUIDS IF VICTIM IS UNCONSCIOUS OR HAVING CONVULSIONS. SEEK IMMEDIATE MEDICAL ATTENTION.

## SECTION V - FIRE-FIGHTING MEASURES

Flammability Class	IIIB
Flash Range:	>200F Pensky-Martens Closed Cup ASTM D 93
Explosive Range:	Not Available

## SECTION VI - ACCIDENTAL RELEASE MEASURES

### SPILLS:

SHUT OFF ALL IGNITION SOURCES AND DIKE SPILL TO CONTAIN AND

---

# MATERIAL SAFETY DATA SHEET

MSDS Name: KALEX 16552 PART B  
MSDS Number: 16552-2  
Version Number: F  
MSDS Date: JUN-20-2005  
Page Number: 3 of 5

---

PREVENT ENTRY INTO SEWERS OR WATER SOURCES. ABSORB SPILLED MATERIAL AND PLACE IN CLOSED CONTAINER FOR DISPOSAL. CONTROLLED INCINERATION. HANDLE IN COMPLIANCE WITH LOCAL, STATE, AND FEDERAL ENVIRONMENTAL PROTECTION AGENCY REGULATIONS.

## SECTION VII - HANDLING AND STORAGE

### STORAGE CONDITIONS:

STORE IN A COOL, DRY PLACE. KEEP AWAY FROM OPEN FLAMES AND HIGH TEMPERATURES.

## SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

### Occupational Exposure Limits

	ACGIH TLV	ACGIH TLV-C	ACGIH STEL	OSHA STEL	OSHA PEL
POLYBUTADIENE	N/est	N/est	N/est	N/est	N/est
HYDRATED ALUMINA	10.0000 mg/M3	N/est	N/est	N/est	15.5000 mg/M3
TRADE SECRET	N/est	N/est	N/est	N/est	N/est
TRADE SECRET	N/est	N/est	N/est	N/est	N/est
TRADE SECRET	N/est	N/est	N/est	N/est	N/est
TRADE SECRET	N/est	N/est	N/est	N/est	N/est
FUMED SILICA	10.0000 mg/M3	N/est	N/est	N/est	N/est

### PERSONAL PROTECTIVE EQUIPMENT:

IN THE ABSENCE OF PROPER ENVIRONMENTAL CONTROL OR VENTILATION, WEAR A RESPIRATOR APPROVED BY NIOSH/MSHA WHENEVER EXPOSED TO FUMES OR VAPORS. COMPLY WITH OSHA 1910.134 (CFR). SELF-CONTAINED BREATHING APPARATUS IN HIGH CONCENTRATIONS. LOCAL EXHAUST IS RECOMMENDED. USE CHEMICAL RESISTANT PROTECTIVE GLOVES, CHEMICAL SPLASH GOGGLES.

---

# MATERIAL SAFETY DATA SHEET

MSDS Name: KALEX 16552 PART B  
MSDS Number: 16552-2  
Version Number: F  
MSDS Date: JUN-20-2005  
Page Number: 4 of 5

---

CHEMICAL RESISTANT PROTECTIVE CLOTHING TO MINIMIZE EXPOSURE;  
CHEMICAL SPLASH APRON, FULL FACE SHIELD. EYE WASH STATION AND  
SAFETY SHOWER SHOULD BE AVAILABLE FOR EMERGENCY USE.

## SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

Form: LIQUID  
Boiling Range: Not Available  
Vapor Pressure (mmHg): Not Available  
Melting Point: Not Applicable  
Evaporation Rate: Unavailable  
  
% Volatile: Not Available  
Specific Gravity: 1.44

## SECTION X - STABILITY AND REACTIVITY

Stability: This product is stable  
Hazardous Polymerization: Hazardous polymerization will not occur

## SECTION XI - TOXICOLOGICAL INFORMATION

Lethal Dose Information (ppm)	Oral	Skin	Inhale	LC50
-------------------------------	------	------	--------	------

## SECTION XII - ECOLOGICAL INFORMATION

NO INFORMATION IS AVAILABLE.

## SECTION XIII - DISPOSAL CONSIDERATIONS

### RCRA CONSIDERATIONS:

THIS PRODUCT IF DISPOSED OF IN THE PURCHASED FORM IS NOT CONSIDERED  
RCRA HAZARDOUS.

## SECTION XIV - TRANSPORT INFORMATION

UN Number  
UN Pack Group  
UN Class  
ICAO/IATA Class: NOT REGULATED

---

# MATERIAL SAFETY DATA SHEET

MSDS Name: KALEX 16552 PART B  
MSDS Number: 16552-2  
Version Number F  
MSDS Date: JUN-20-2005  
Page Number: 5 of 5

---

IMDG Class	NOT REGULATED
Shipping Name	PLASTIC LIQUID, NOS
ADR/RID Class	NOT REGULATED
DOT Hazard Class	
Technical Name	

## SECTION XV - REGULATORY INFORMATION

### TSCA STATUS:

ALL INGREDIENTS CONTAINED IN THIS PRODUCT ARE ON THE TSCA INVENTORY.

## SECTION XVI - OTHER INFORMATION

### DISCLAIMER:

ALTHOUGH THE INFORMATION AND RECOMMENDATIONS SET FORTH HEREIN (HEREINAFTER "INFORMATION") ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE CORRECT AS OF THE DATE HEREOF, ROYAL ADHESIVES & SEALANTS LLC MAKES NO REPRESENTATIONS AS TO THE COMPLETENESS OR ACCURACY THEREOF. INFORMATION IS SUPPLIED UPON THE CONDITION THAT THE PERSONS RECEIVING SAME WILL MAKE THEIR OWN DETERMINATION AS TO ITS SUITABILITY FOR THEIR PURPOSES PRIOR TO USE. IN NO EVENT WILL ROYAL ADHESIVES & SEALANTS LLC BE RESPONSIBLE FOR DAMAGES OF ANY NATURE WHATSOEVER RESULTING FROM THE USE OF OR RELIANCE UPON INFORMATION. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OF ANY NATURE ARE MADE HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT TO WHICH INFORMATION REFERS.