

# MATERIAL SAFETY DATA SHEET

MSDS Name: KALEX 16324 PART A  
MSDS Number: 16324-1  
Version Number: F  
MSDS Date: JUL-01-2005  
Page Number: 1 of 7

---

## SECTION I - PRODUCT AND COMPANY INFORMATION

Product Name: KALEX 16324 PART A  
Hazard Rating: Health: 3 Fire: 1 Reactivity: 1 PPI:

Company Identification: ROYAL ADHESIVES & SEALANTS LLC  
600 CORTLANDT STREET  
BELLEVILLE NJ 07109-3384

Contact: BRUCE WEINMAN  
Telephone/Fax: (973) 751-3000 (973) 751-8407  
Emergency Phone (24 Hour): ENVIRONMENTAL SPECIALIST  
(973) 751-3000  
Chemtrec (24 Hour): (800) 424-9300  
Preparer: B. WEINMAN  
ENVIRONMENTAL SPECIALIST

Product Class: POLYMERIC DIISOCYANATE  
Trade Name: KALEX 16324 PART A  
Product Code: 16324-1

## SECTION II - INGREDIENT AND HAZARD INFORMATION

| Hazardous Ingredients             | CAS Number   |
|-----------------------------------|--------------|
| TRADE SECRET                      | TRADE SECRET |
| 4,4'-DIPHENYLMETHANE DIISOCYANATE | 101-68-8     |
| TRADE SECRET                      | TRADE SECRET |

\*\*\* ALL Ingredients in this product are listed in the T.S.C.A. Inventory

## SECTION III - HAZARDS IDENTIFICATION

### HEALTH HAZARD INFORMATION:

#### EYE CONTACT:

MAY CAUSE EYE IRRITATION. CORNEAL DAMAGE POSSIBLE.

#### SKIN CONTACT:

MAY CAUSE IRRITATION. PROLONGED OR REPEATED CONTACT MAY CAUSE RASH, REDDENING, SWELLING, AND IN SOME CASES, SKIN SENSITIZATION.

---

# MATERIAL SAFETY DATA SHEET

MSDS Name: KALEX 16324 PART A  
MSDS Number: 16324-1  
Version Number F  
MSDS Date: JUL-01-2005  
Page Number: 2 of 7

---

## INHALATION:

AT ROOM TEMPERATURE VAPORS ARE MINIMAL DUE TO LOW VAPOR PRESSURE. HOWEVER, HEATING OR SPRAYING MAY GENERATE VAPOR CONCENTRATIONS SUFFICIENT TO CAUSE IRRITATION. EXCESSIVE EXPOSURE MAY CAUSE IRRITATION OF THE EYES, UPPER RESPIRATORY TRACT, AND LUNGS. MAY CAUSE RESPIRATORY SENSITIZATION IN SUSCEPTIBLE INDIVIDUALS. MDI CONCENTRATIONS BELOW THE EXPOSURE GUIDELINES MAY CAUSE ALLERGIC RESPIRATORY REACTIONS IN INDIVIDUALS ALREADY SENSITIZED. SYMPTOMS MAY INCLUDE COUGHING, DIFFICULT BREATHING AND A FEELING OF TIGHTNESS IN THE CHEST. EFFECTS MAY BE DELAYED. IMPAIRED LUNG FUNCTION (DECREASED VENTILATORY CAPACITY) HAS BEEN ASSOCIATED WITH OVEREXPOSURE TO ISOCYANATES.

## INGESTION:

MAY CAUSE IRRITATION AND CORROSIVE ACTION IN THE MOUTH, STOMACH TISSUE AND DIGESTIVE TRACT. SYMPTOMS CAN INCLUDE SORE THROAT, ABDOMINAL PAIN, NAUSEA, VOMITING AND DIARRHEA.

## OTHER HEALTH INFORMATION (POLYMERIC MDI CAS 101-68-8):

TISSUE INJURY IN THE UPPER RESPIRATORY TRACT AND LUNGS HAS BEEN OBSERVED IN LABORATORY ANIMALS AFTER REPEATED EXCESSIVE EXPOSURES TO MDI/POLYMERIC MDI AEROSOLS.

LUNG TUMORS HAVE BEEN OBSERVED IN LABORATORY ANIMALS EXPOSED TO AEROSOL DROPLETS OF MDI/POLYMERIC MDI FOR THEIR LIFETIME. TUMORS OCCURRED CONCURRENTLY WITH RESPIRATORY IRRITATION AND LUNG INJURY. CURRENT EXPOSURE GUIDELINES ARE EXPECTED TO PROTECT AGAINST THESE EFFECTS REPORTED FOR MDI.

IN LABORATORY ANIMALS, MDI/POLYMERIC MDI DID NOT PRODUCE BIRTH DEFECTS; OTHER FETAL EFFECTS OCCURRED ONLY AT HIGH DOSES WHICH WERE TOXIC TO THE MOTHER.

ANIMAL TESTS HAVE ALSO INDICATED THAT RESPIRATORY SENSITIZATION CAN RESULT FROM SKIN CONTACT WITH MDI. USE SKIN PROTECTION.

## SECTION IV - FIRST AID MEASURES

### EYES:

WASH WITH FLOWING WATER IMMEDIATELY AND CONTINUOUSLY FOR 15 MINUTES. CONSULT MEDICAL PERSONNEL.

### SKIN:

WASH WITH SOAP AND PLENTY OF WARM WATER.

---

# MATERIAL SAFETY DATA SHEET

MSDS Name: KALEX 16324 PART A  
MSDS Number: 16324-1  
Version Number F  
MSDS Date: JUL-01-2005  
Page Number: 3 of 7

---

## INHALATION:

REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. IF BREATHING IS DIFFICULT, OXYGEN SHOULD BE ADMINISTERED BY QUALIFIED PERSONNEL. CALL A PHYSICIAN OR TRANSPORT TO A MEDICAL FACILITY.

## INGESTION:

IF SWALLOWED SEEK MEDICAL ATTENTION. DO NOT INDUCE VOMITING UNLESS DIRECTED TO DO SO BY MEDICAL PERSONNEL. GIVE NOTHING BY MOUTH IF PERSON IS UNCONSCIOUS OR HAVING CONVULSIONS.

## SECTION V - FIRE-FIGHTING MEASURES

|                    |                                     |
|--------------------|-------------------------------------|
| Flammability Class | IIIB                                |
| Flash Range:       | Not Available                       |
|                    | Pensky-Martens Closed Cup ASTM D 93 |
|                    | >200F                               |
| Explosive Range:   | Not Available                       |

### FIRE-FIGHTING MEASURES:

WATER SPRAY  
DRY CHEMICAL  
FOAM  
CARBON DIOXIDE  
USE FULL TURNOUT GEAR INCLUDING SELF-CONTAINED BREATHING APPARATUS (SCBA).  
DURING A FIRE, POLYMERIC DIPHENYLMETHANE DIISOCYANATE (MDI) VAPORS AND OTHER IRRITATING, HIGHLY TOXIC GASES MAY BE GENERATED BY THERMAL DECOMPOSITION OR COMBUSTION. AT TEMPERATURES GREATER THAN 400F, POLYMERIC MDI CAN POLYMERIZE AND DECOMPOSE WHICH CAN CAUSE PRESSURE BUILD-UP IN CLOSED CONTAINERS. EXPLOSIVE RUPTURE IS POSSIBLE. THEREFORE, USE COLD WATER TO COOL FIRE-EXPOSED CONTAINERS.

## SECTION VI - ACCIDENTAL RELEASE MEASURES

### SPILLS:

SHUT OFF ALL IGNITION SOURCES AND DIKE SPILL TO CONTAIN AND PREVENT ENTRY INTO SEWERS OR WATER SOURCES. ABSORB SPILLED MATERIAL AND PLACE INTO OPEN TOP CONTAINERS. DO NOT MAKE PRESSURE TIGHT. TRANSPORT TO A WELL-VENTILATED AREA (OUTSIDE) AND TREAT WITH NEUTRALIZING SOLUTION CONSISTING OF A MIXTURE OF 85% WATER, 5% CONCENTRATED AMMONIUM HYDROXIDE AND 10% SODIUM

---

# MATERIAL SAFETY DATA SHEET

MSDS Name: KALEX 16324 PART A  
MSDS Number: 16324-1  
Version Number: F  
MSDS Date: JUL-01-2005  
Page Number: 4 of 7

-----

CARBONATE. ADD ABOUT 10 PARTS OF NEUTRALIZER PER PART OF ISO-CYANATE WITH MIXING. ALLOW TO STAND FOR 48 HOURS LETTING EVOLVED CARBON DIOXIDE TO ESCAPE. IF TEMPORARY CONTROL OF ISOCYANATE VAPOR IS REQUIRED, A BLANKET OF PROTEIN FOAM (AVAILABLE AT MOST FIRE DEPARTMENTS) MAY BE PLACED OVER THE SPILL. CONTROLLED INCINERATION. HANDLE IN COMPLIANCE WITH LOCAL, STATE, AND FEDERAL ENVIRONMENTAL PROTECTION AGENCY REGULATIONS.

## SECTION VII - HANDLING AND STORAGE

### STORAGE CONDITIONS:

STORE IN TIGHTLY CLOSED CONTAINERS TO PREVENT MOISTURE CONTAMINATION. DO NOT RESEAL IF CONTAMINATION IS SUSPECTED. OPTIMUM STORAGE TEMPERATURE IS 80F TO 100F.

## SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

### Occupational Exposure Limits

|                                   | ACGIH TLV  | ACGIH TLV-C | ACGIH STEL | OSHA STEL | OSHA PEL   |
|-----------------------------------|------------|-------------|------------|-----------|------------|
| TRADE SECRET                      |            |             |            |           |            |
|                                   | N/est      | N/est       | N/est      | N/est     | N/est      |
| 4,4'-DIPHENYLMETHANE DIISOCYANATE |            |             |            |           |            |
|                                   | 0.0050 PPM | N/est       | N/est      | N/est     | 0.0200 PPM |
| TRADE SECRET                      |            |             |            |           |            |
|                                   | N/est      | N/est       | N/est      | N/est     | N/est      |

### PERSONAL PROTECTIVE EQUIPMENT:

ATMOSPHERIC LEVELS SHOULD BE MAINTAINED BELOW THE EXPOSURE GUIDE LINE. WHEN RESPIRATORY PROTECTION IS REQUIRED FOR CERTAIN OPERATIONS, USE AN APPROVED POSITIVE-PRESSURE SUPPLIED-AIR RESPIRATOR. FOR EMERGENCY AND OTHER CONDITIONS WHERE THE EXPOSURE GUIDELINE MAY BE GREATLY EXCEEDED, USE AN APPROVED POSITIVE-PRESSURE SELF-CONTAINED BREATHING APPARATUS OR POSITIVE-PRESSURE AIRLINE WITH AUXILIARY SELF-CONTAINED AIR SUPPLY. THIS PRODUCT HAS POOR WARNING PROPERTIES, SINCE RECOGNITION OF AN ODOR IS FAR ABOVE THE TLV. OBSERVE OSHA REGULATIONS FOR RESPIRATOR USE (29 CFR 1910.134). LOCAL EXHAUST IS RECOMMENDED. USE PROTECTIVE CLOTHING IMPERVIOUS TO THIS MATERIAL. SELECTION OF SPECIFIC ITEMS SUCH AS FACESHIELD, GLOVES, OR APRON WILL DEPEND ON OPERATION.

-----

# MATERIAL SAFETY DATA SHEET

MSDS Name: KALEX 16324 PART A  
MSDS Number: 16324-1  
Version Number: F  
MSDS Date: JUL-01-2005  
Page Number: 5 of 7

---

CHEMICAL SPLASH GOGGLES. IN A SPLASH ENVIRONMENT CHEMICAL GOGGLES AND FULL FACE SHIELD SHOULD BE WORN. CHEMICAL RESISTANT PROTECTIVE CLOTHING TO MINIMIZE EXPOSURE. EYE WASH STATION AND SAFETY SHOWER SHOULD BE AVAILABLE FOR EMERGENCY USE.

## SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

Form: LIQUID  
Boiling Range: Not Available  
Vapor Pressure (mmHg): Not Available  
Melting Point: Not Applicable  
Evaporation Rate: Unavailable  
  
% Volatile: Not Available  
Specific Gravity: 1.14

## SECTION X - STABILITY AND REACTIVITY

Stability: This product is stable  
Hazardous Polymerization: Hazardous polymerization may occur

### REACTIVITY:

#### INCOMPATIBILITY:

OXIDIZING AGENTS  
AMINES  
ALCOHOLS  
WATER  
ACIDS AND CAUSTIC ALKALI SOLUTIONS.

#### CONDITIONS TO AVOID:

HIGH TEMPERATURES.

#### HAZARDOUS DECOMPOSITION PRODUCTS:

CARBON MONOXIDE, CARBON DIOXIDE, ISOCYANATE-CONTAINING VAPOR.

## SECTION XI - TOXICOLOGICAL INFORMATION

| Lethal Dose Information (ppm) | Oral | Skin | Inhale | LC50 |
|-------------------------------|------|------|--------|------|
|-------------------------------|------|------|--------|------|

## SECTION XII - ECOLOGICAL INFORMATION

---

# MATERIAL SAFETY DATA SHEET

MSDS Name: KALEX 16324 PART A  
MSDS Number: 16324-1  
Version Number F  
MSDS Date: JUL-01-2005  
Page Number: 6 of 7

---

NO INFORMATION IS AVAILABLE.

## SECTION XIII - DISPOSAL CONSIDERATIONS

### RCRA CONSIDERATIONS:

THIS PRODUCT IF DISPOSED OF IN THE PURCHASED FORM IS NOT CONSIDERED RCRA HAZARDOUS.

## SECTION XIV - TRANSPORT INFORMATION

UN Number  
UN Pack Group  
UN Class  
ICAO/IATA Class NOT REGULATED  
IMDG Class NOT REGULATED  
Shipping Name PLASTIC LIQUID, NOS  
ADR/RID Class NOT REGULATED  
DOT Hazard Class  
Technical Name

## SECTION XV - REGULATORY INFORMATION

### SARA TITLE III SECTION 313:

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right to Know Act of 1986 and of 40 CFR 372:

| Chemical Name                     | CAS Number | %      |
|-----------------------------------|------------|--------|
| 4,4'-DIPHENYLMETHANE DIISOCYANATE | 101-68-8   | 10 -15 |

### TSCA STATUS:

ALL INGREDIENTS CONTAINED IN THIS PRODUCT ARE ON THE TSCA INVENTORY.

### INVENTORY STATUS:

ALL THE COMPONENT(S) OF THIS PRODUCT HAVE BEEN FOUND ON THE FOLLOWING INVENTORIES:

UNITED STATES

ALL THE COMPONENT(S) OF THIS PRODUCT HAVE NOT YET BEEN IDENTIFIED

---

# MATERIAL SAFETY DATA SHEET

MSDS Name: KALEX 16324 PART A  
MSDS Number: 16324-1  
Version Number F  
MSDS Date: JUL-01-2005  
Page Number: 7 of 7

---

ON THE FOLLOWING INVENTORIES:

EUROPE  
CANADA  
AUSTRALIA  
JAPAN  
KOREA  
CHINA  
PHILIPPINES

## SECTION XVI - OTHER INFORMATION

DISCLAIMER:

ALTHOUGH THE INFORMATION AND RECOMMENDATIONS SET FORTH HEREIN (HEREINAFTER "INFORMATION") ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE CORRECT AS OF THE DATE HEREOF, ROYAL ADHESIVES & SEALANTS LLC MAKES NO REPRESENTATIONS AS TO THE COMPLETENESS OR ACCURACY THEREOF. INFORMATION IS SUPPLIED UPON THE CONDITION THAT THE PERSONS RECEIVING SAME WILL MAKE THEIR OWN DETERMINATION AS TO ITS SUITABILITY FOR THEIR PURPOSES PRIOR TO USE. IN NO EVENT WILL ROYAL ADHESIVES & SEALANTS LLC BE RESPONSIBLE FOR DAMAGES OF ANY NATURE WHATSOEVER RESULTING FROM THE USE OF OR RELIANCE UPON INFORMATION. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OF ANY NATURE ARE MADE HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT TO WHICH INFORMATION REFERS.

# MATERIAL SAFETY DATA SHEET

MSDS Name: KALEX 16324 PART B  
MSDS Number: 16324-2  
Version Number: F  
MSDS Date: JUL-01-2005  
Page Number: 1 of 5

---

## SECTION I - PRODUCT AND COMPANY INFORMATION

Product Name: KALEX 16324 PART B  
Hazard Rating: Health: 2 Fire: 1 Reactivity: 0 PPI:

Company Identification: ROYAL ADHESIVES & SEALANTS LLC  
600 CORTLANDT STREET  
BELLEVILLE NJ 07109-3384

Contact: BRUCE WEINMAN  
Telephone/Fax: (973) 751-3000 (973) 751-8407  
Emergency Phone (24 Hour): ENVIRONMENTAL SPECIALIST  
(973) 751-3000  
Chemtrec (24 Hour): (800) 424-9300  
Preparer: B. WEINMAN  
ENVIRONMENTAL SPECIALIST

Product Class: POLYOL  
Trade Name: KALEX 16324 PART B  
Product Code: 16324-2

## SECTION II - INGREDIENT AND HAZARD INFORMATION

Hazardous Ingredients CAS Number

TRADE SECRET

TRADE SECRET

\*\*\* ALL Ingredients in this product are listed in the T.S.C.A. Inventory

## SECTION III - HAZARDS IDENTIFICATION

EYE CONTACT:

MAY CAUSE MINOR EYE IRRITATION.

SKIN CONTACT:

MAY CAUSE SLIGHT SKIN IRRITATION.

INHALATION:

THIS PRODUCT IS NOT EXPECTED TO BE AN INHALATION HAZARD.

INGESTION:

NO SIGNIFICANT SIGNS OR SYMPTONS INDICATIVE OF ANY ADVERSE HEALTH EFFECT ARE EXPECTED TO OCCUR AS A RESULT OF INGESTION.

---

# MATERIAL SAFETY DATA SHEET

MSDS Name: KALEX 16324 PART B  
MSDS Number: 16324-2  
Version Number F  
MSDS Date: JUL-01-2005  
Page Number: 2 of 5

---

## SECTION IV - FIRST AID MEASURES

**EYES:**  
IMMEDIATELY WASH WITH RUNNING WATER FOR AT LEAST 15 MINUTES. GET IMMEDIATE MEDICAL ATTENTION.

**SKIN:**  
WASH AFFECTED AREAS WITH SOAP AND PLENTY OF WATER. REMOVE AND LAUNDRER CONTAMINATED CLOTHING BEFORE REUSE. GET MEDICAL ATTENTION IF IRRITATION DEVELOPS.

**INHALATION:**  
MOVE PERSON TO FRESH AIR. AID IN BREATHING, GIVE OXYGEN IF NECESSARY. GET IMMEDIATE MEDICAL ATTENTION.

**INGESTION:**  
DRINK TWO GLASSES OF WATER AND IMMEDIATELY INDUCE VOMITING. NEVER GIVE FLUIDS IF VICTIM IS UNCONSCIOUS OR HAVING CONVULSIONS. SEEK IMMEDIATE MEDICAL ATTENTION.

## SECTION V - FIRE-FIGHTING MEASURES

Flammability Class IIIIB  
Flash Range: >200F  
Pensky-Martens Closed Cup ASTM D 93  
Explosive Range: Not Available

**FIRE-FIGHTING MEASURES:**  
USE WATER FOG, DRY CHEMICAL, FOAM, CARBON DIOXIDE. WATER OR FOAM MAY CAUSE FROTHING. USE WATER TO COOL FIRE-EXPOSED CONTAINERS. IF A LEAK OR SPILL HAS NOT IGNITED, USE WATER SPRAY TO DISPERSE THE VAPORS AND PROVIDE PROTECTION TO THE PEOPLE ATTEMPTING TO STOP THE LEAK. USE FULL TURNOUT GEAR INCLUDING SELF-CONTAINED BREATHING APPARATUS (SCBA). FIRE EXPOSED CONTAINERS MAY BUILD PRESSURE AND BURST.

## SECTION VI - ACCIDENTAL RELEASE MEASURES

**SPILLS:**  
SHUT OFF ALL IGNITION SOURCES AND DIKE SPILL TO CONTAIN AND PREVENT ENTRY INTO SEWERS OR WATER SOURCES. ABSORB SPILLED

---

# MATERIAL SAFETY DATA SHEET

MSDS Name: KALEX 16324 PART B  
MSDS Number: 16324-2  
Version Number: F  
MSDS Date: JUL-01-2005  
Page Number: 3 of 5

---

MATERIAL AND PLACE IN CLOSED CONTAINER FOR DISPOSAL.  
CONTROLLED INCINERATION. HANDLE IN COMPLIANCE WITH LOCAL, STATE,  
AND FEDERAL ENVIRONMENTAL PROTECTION AGENCY REGULATIONS.

## SECTION VII - HANDLING AND STORAGE

### STORAGE CONDITIONS:

STORE IN A COOL, DRY PLACE. KEEP AWAY FROM OPEN FLAMES AND HIGH TEMPERATURES.

## SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

| Occupational Exposure Limits | ACGIH TLV | ACGIH TLV-C | ACGIH STEL | OSHA STEL | OSHA PEL |
|------------------------------|-----------|-------------|------------|-----------|----------|
| TRADE SECRET                 | N/est     | N/est       | N/est      | N/est     | N/est    |

### PERSONAL PROTECTIVE EQUIPMENT:

IN THE ABSENCE OF PROPER ENVIRONMENTAL CONTROL OR VENTILATION, WEAR A RESPIRATOR APPROVED BY NIOSH/MSHA WHENEVER EXPOSED TO FUMES OR VAPORS. COMPLY WITH OSHA 1910.134 (CFR). SELF-CONTAINED BREATHING APPARATUS IN HIGH CONCENTRATIONS. LOCAL EXHAUST IS RECOMMENDED. USE CHEMICAL RESISTANT PROTECTIVE GLOVES, CHEMICAL SPLASH GOGGLES. CHEMICAL RESISTANT PROTECTIVE CLOTHING TO MINIMIZE EXPOSURE; CHEMICAL SPLASH APRON, FULL FACE SHIELD. EYE WASH STATION AND SAFETY SHOWER SHOULD BE AVAILABLE FOR EMERGENCY USE.

## SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

|                        |                |
|------------------------|----------------|
| Form:                  | LIQUID         |
| Boiling Range:         | Not Available  |
| Vapor Pressure (mmHg): | Not Available  |
| Melting Point:         | Not Applicable |
| Evaporation Rate:      | Unavailable    |
| % Volatile             | Not Available  |
| Specific Gravity:      | 0.96           |

## SECTION X - STABILITY AND REACTIVITY

Stability: This product is stable

---

# MATERIAL SAFETY DATA SHEET

MSDS Name: KALEX 16324 PART B  
MSDS Number: 16324-2  
Version Number F  
MSDS Date: JUL-01-2005  
Page Number: 4 of 5

---

Hazardous Polymerization: Hazardous polymerization will not occur

## REACTIVITY:

INCOMPATIBILITY:  
OXIDIZING AGENTS, WATER.  
CONDITIONS TO AVOID:  
HIGH TEMPERATURES.  
HAZARDOUS DECOMPOSITION PRODUCTS:  
CARBON MONOXIDE, CARBON DIOXIDE.

## SECTION XI - TOXICOLOGICAL INFORMATION

| Lethal Dose Information (ppm) | Oral | Skin | Inhale | LC50 |
|-------------------------------|------|------|--------|------|
|-------------------------------|------|------|--------|------|

TOXICOLOGICAL INFORMATION:  
NO INFORMATION IS AVAILABLE.

## SECTION XII - ECOLOGICAL INFORMATION

NO INFORMATION IS AVAILABLE.

## SECTION XIII - DISPOSAL CONSIDERATIONS

### RCRA CONSIDERATIONS:

THIS PRODUCT IF DISPOSED OF IN THE PURCHASED FORM IS NOT CONSIDERED RCRA HAZARDOUS.

## SECTION XIV - TRANSPORT INFORMATION

|                  |                     |
|------------------|---------------------|
| UN Number        |                     |
| UN Pack Group    |                     |
| UN Class         |                     |
| ICAO/IATA Class  | NOT REGULATED       |
| IMDG Class       | NOT REGULATED       |
| Shipping Name    | PLASTIC LIQUID, NOS |
| ADR/RID Class    | NOT REGULATED       |
| DOT Hazard Class |                     |
| Technical Name   |                     |

## SECTION XV - REGULATORY INFORMATION

---

# MATERIAL SAFETY DATA SHEET

MSDS Name: KALEX 16324 PART B  
MSDS Number: 16324-2  
Version Number F  
MSDS Date: JUL-01-2005  
Page Number: 5 of 5

---

## **TSCA STATUS:**

ALL INGREDIENTS CONTAINED IN THIS PRODUCT ARE ON THE TSCA INVENTORY.

## INVENTORY STATUS:

ALL THE COMPONENT(S) OF THIS PRODUCT HAVE BEEN FOUND ON THE FOLLOWING INVENTORIES:

UNITED STATES

ALL THE COMPONENT(S) OF THIS PRODUCT HAVE NOT YET BEEN IDENTIFIED ON THE FOLLOWING INVENTORIES:

EUROPE  
CANADA  
AUSTRALIA  
JAPAN  
KOREA  
CHINA  
PHILIPPINES

## **SECTION XVI - OTHER INFORMATION**

### DISCLAIMER:

ALTHOUGH THE INFORMATION AND RECOMMENDATIONS SET FORTH HEREIN (HEREINAFTER "INFORMATION") ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE CORRECT AS OF THE DATE HEREOF, ROYAL ADHESIVES & SEALANTS LLC MAKES NO REPRESENTATIONS AS TO THE COMPLETENESS OR ACCURACY THEREOF. INFORMATION IS SUPPLIED UPON THE CONDITION THAT THE PERSONS RECEIVING SAME WILL MAKE THEIR OWN DETERMINATION AS TO ITS SUITABILITY FOR THEIR PURPOSES PRIOR TO USE. IN NO EVENT WILL ROYAL ADHESIVES & SEALANTS LLC BE RESPONSIBLE FOR DAMAGES OF ANY NATURE WHATSOEVER RESULTING FROM THE USE OF OR RELIANCE UPON INFORMATION. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OF ANY NATURE ARE MADE HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT TO WHICH INFORMATION REFERS.